

Data sheet - V.07.23

SP-T Sprinter Turntable



GLOBAL
VACUUM PRESSES

SP-T

Sprinter Turntable

Model	SP-T-2513	SP-T-3113	SP-T-3713
Press area	2x 2560 x 1310 mm	2x 3160 x 1310 mm	2x 3760 x 1310 mm
Operation	Manual operation Rotation by gear motor drive Vacuum switch for AUTOMATIC / OFF / CONTINUOUS 2 vacuum control valves Digital temperature control unit		
Heating hood	Insulated heating station, double wall design 6 durable tubular heating elements Max. heating temperature 100 °C		
Vacuum pump	40 m ³ /h vacuum pump Rotary vane, oil-free Digital pressure switch (auto power ON/OFF)		
Max. pressure	8.5 t/m ² = 150 mbar abs (85% Vacuum)		
Membrane	NR	NR	NR
Work top	13 mm wear- and heat-resistant HPL compact board Grid line raster for even air evacuation Working height 900 mm		
Supports	Adjustable anti-slip feet		
Security system	Two hand control Emergency Stop		
Elec. connection	220/400V, 3~, 50/60 Hz		
Max. power	12 kW	14.5 kW	17 kW
Dimensions	3630 x 1650 x 1175 mm	4230 x 1650 x 1175 mm	4830 x 1650 x 1175 mm
Weight	1210 kg	1350 kg	1490 kg
Certification	CE – Declaration of conformity CO – Certificate of origin (on request)		

Technical information may differ slightly

NR = Natural rubber

Optional features

- Two 250 mm high volume silicone membrane
- 40 m³/h Oil lubricated vacuum pump